

Active Directory Integrations

Introduction

Elastic Stack security features can be configured to authenticate users through Active Directory by using LDAP to communicate with the directory. Active Directory realms are similar to LDAP realms, as they both store users and groups in a hierarchical structure, which includes containers such as organizational units (OU), organizations (O), and domain components (DC).


The security features support authentication based on Active Directory security groups, but not distribution groups. When authenticating users, the username entered must match the sAMAccountName or userPrincipalName, not the common name (cn). The realm authenticates users via an LDAP bind request, searches for their entry in Active Directory, and retrieves their group memberships from the tokenGroups attribute to assign appropriate roles.

I. Active Directory Information Lookup


Finding the Base DN (Distinguished Name)

Method 1: Using Active Directory GUI


1. Open "Active Directory Users and Computers"




2. Right-click on your domain



3. Select "Properties"



4. Look for the "Distinguished Name" field



Method 2: Using PowerShell

1. Open PowerShell with administrator privileges
2. Run the command:

```
Get-ADDomain | Select-Object DistinguishedName
```

3. The output will be in the format: "DC=company,DC=local"

II. Finding Active Directory URL



Method 1: PowerShell

1. Open PowerShell as administrator
2. Run the command:

```
Get-ADDomainController | Select-Object HostName
```

3. Take the DC name from the output
 - [LDAP://servername.domain.com](#)
 - [LDAP://server-IP](#)

III. Navigate to Users



If you need further assistance, kindly contact our support at info@cytechint.com for prompt assistance and guidance.

Revision #4

Created 13 November 2024 10:21:44 by CyTech Admin

Updated 14 November 2024 08:19:02 by David Napoleon Romanillos