

Azure Application Insights Integration

The **Application Insights Integration** allows users to collect metrics from Azure Application Insights.

Key Configuration Options:

- **Application ID:** The ID of the application from the API Access settings in the Azure portal.
- **API Key:** A generated key for authentication.

Data Stream: `app_insights`

Users can retrieve various metrics with filtering options.

Configuration Options:

- **Metrics:** List of metrics to collect.
- **ID:** Metric IDs or names. Default includes requests, performance, and availability.
- **Interval:** ISO8601 duration for metric retrieval. Defaults to entire timespan if omitted.
- **Aggregation:** Functions like sum, average, etc. Defaults to metric-specific aggregation.
- **Segment:** Dimension to group metric data by.
- **Top:** Number of segments to return (valid only with `segment`).
- **Order By:** Sorting order for segments (valid only with `segment`).
- **Filter:** OData filter expression for refining results.

An example event for `app_insights` looks as following:

```
{
  "@timestamp": "2021-08-23T14:37:42.268Z",
  "agent": {
    "ephemeral_id": "4162d5df-ab00-4c1b-b4f3-7db2e3b599d4",
    "hostname": "docker-fleet-agent",
    "id": "d979a8cf-ddeb-458f-9019-389414e0ab47",
    "name": "docker-fleet-agent",
    "type": "metricbeat",
```

```
    "version": "7.15.0"
  },
  "azure": {
    "app_insights": {
      "end_date": "2021-08-23T14:37:42.268Z",
      "start_date": "2021-08-23T14:32:42.268Z"
    },
    "application_id": "42cb59a9-d5be-400b-a5c4-69b0a0026ac6",
    "dimensions": {
      "request_name": "GET Home/Index",
      "request_url_host": "demoappobs.azurewebsites.net"
    },
    "metrics": {
      "requests_count": {
        "sum": 4
      }
    }
  },
  "cloud": {
    "provider": "azure"
  },
  "data_stream": {
    "dataset": "azure.app_insights",
    "namespace": "default",
    "type": "metrics"
  },
  "ecs": {
    "version": "8.11.0"
  },
  "elastic_agent": {
    "id": "d979a8cf-ddeb-458f-9019-389414e0ab47",
    "snapshot": true,
    "version": "7.15.0"
  },
  "event": {
    "agent_id_status": "verified",
    "dataset": "azure.app_insights",
    "duration": 503187300,
    "ingested": "2021-08-23T14:37:41Z",
    "module": "azure"
```

```
},
"host": {
  "architecture": "x86_64",
  "containerized": true,
  "hostname": "docker-fleet-agent",
  "id": "1642d255f9a32fc6926cddf21bb0d5d3",
  "ip": [
    "192.168.96.7"
  ],
  "mac": [
    "02-42-AC-1F-00-07"
  ],
  "name": "docker-fleet-agent",
  "os": {
    "codename": "Core",
    "family": "redhat",
    "kernel": "4.19.128-microsoft-standard",
    "name": "CentOS Linux",
    "platform": "centos",
    "type": "linux",
    "version": "7 (Core)"
  }
},
"metricset": {
  "name": "app_insights",
  "period": 300000
},
"service": {
  "type": "azure"
}
}
```

Revision #1

Created 17 March 2025 06:41:47 by Richmond Abella

Updated 17 March 2025 06:58:09 by Richmond Abella