CyberArk PAM

Configure the Vault to Forward syslog Messages to PTA

The system logger of the Vault must be configured to send logging data to the PTA machine for real-time data analysis.

	When PTA is configured with Vaults deployed in a distributed environment, configure the primary and satellite Vaults.

To Configure syslog on the Vault Machine (until Vault v10.4):

	1.	From the installation package, copy PTA.xsl to the Syslog subdirectory of the Vault installation folder. By default, the subdirectory is: C:\Program Files (x86)\PrivateArk\Server\Syslog.

	2.	In the same server installation folder,by default C:\Program Files (x86)\PrivateArk\Server, open dbparm.ini and add the following lines:

[SYSLOG]
SyslogTranslatorFile=Syslog\PTA.xsl
SyslogServerPort=<port number>
SyslogServerIP=<server IP>
SyslogServerProtocol=UDP
SyslogMessageCodeFilter=295,308,7,24,31,428,361,372,373,359,436,412,411,300,302,294,427
UseLegacySyslogFormat=No

Specify the following information:

Parameter Name	Define or Select
SyslogServerIP	The IP address(es) of the PTA machine where messages will be sent.
SyslogServerPort	The port number through which the syslog will be sent. Specify 514 to send syslogs to the default PTA port.

<table>
<tr><th>Parameter Name</th><th>Define or Select</th></tr>
<tr><td>SyslogServerProtocol</td><td>The protocol used to transfer the syslog records.
Specify: tcp or udp.<table><tr><td></td><td>PTA does not support the SSL protocol.</td></tr></table></td></tr>
<tr><td>SyslogMessageCodeFilter</td><td>Defines which message codes will be sent from the Vault Machine to PTA through Syslog protocol.
You can specify message numbers, separated by commas.
You can also specify range of numbers using ‘-‘.
Message codes are sent for the following events:<table><tr><th>Code</th><th>Activity</th></tr><tr><td>7</td><td>Logon</td></tr><tr><td>24</td><td>CPM Change Password</td></tr><tr><td>31</td><td>CPM Reconcile Password</td></tr><tr><td>295</td><td>Retrieve Password</td></tr><tr><td>308</td><td>Use Password</td></tr><tr><td>428</td><td>Retrieve SSH keys</td></tr><tr><td>361</td><td>SSH Command</td></tr><tr><td>372</td><td>Terminated PSM Session</td></tr><tr><td>373</td><td>Terminated PSM Session Failed</td></tr><tr><td>359</td><td>SQL Command</td></tr><tr><td>436</td><td>SCP Command</td></tr><tr><td>412</td><td>PSM Keystrokes Logging</td></tr><tr><td>411</td><td>PSM Window Titles</td></tr><tr><td>300</td><td>PSM Connect</td></tr><tr><td>302</td><td>PSM Disconnect</td></tr><tr><td>294</td><td>Store Password</td></tr><tr><td>427</td><td>Store SSH Key</td></tr></table></td></tr>
<tr><td>SyslogTranslatorFile</td><td>Specifies the XSL file used to parse Vault records data into Syslog protocol.</td></tr>
<tr><td>UseLegacySyslogFormat</td><td>Controls the format of the syslog message, and defines whether it will be sent in a newer syslog format (RFC 5424) or in a legacy format.
Required value: No. This enables the Vault to work with the newer syslog format.</td></tr>
</table>

	3.	To forward Vault syslogs to multiple machines (for instance to your SIEM solution as well as to PTA), you can specify multiple values for the following parameters and separate each value with a comma.
	■	This requires a CyberArk Vault version 7.2.5 or higher.
	■	All destinations must use the same port and protocol, which are specified in the SyslogServerPort and SyslogServerProtocol fields.
	■	The specified values will apply to all destinations configured in SyslogServerIP, using the translator files specified in SysLogTranslatorFile.

Parameter Name	Comments
SyslogServerIP	
SyslogTranslatorFile	
UseLegacySyslogFormat	
SyslogMessageCodeFilter	Separate multiple values with a comma, and separate sets of multiple values with a pipe-line, as shown in the example below.

The following example shows how to send different syslog messages to multiple syslog servers.

```
[SYSLOG]
SysLogTranslatorFile=Syslog\Arcsight.sample.xsl,Syslog\QRadar.xsl,Syslog\PTA.xsl
SyslogServerPort=<port number>
SysLogServerIP=1.1.1.1,1.1.2.2,1.1.3.3
SyslogServerProtocol=UDP
UseLegacySyslogFormat=Yes,Yes,No
SyslogMessageCodeFilter=7,8,295|295-
```

296|295,308,7,24,31,428,361,372,373,359,436,412,411,300,302,294,427

	4.	Save the file and close it.

	5.	Restart the Vault.

For more detailed instructions about integrating SIEM applications, see Security Information and Event Management Applications.

To Configure syslog on the Vault Machine (from Vault v10.5):

	1.	The PTA syslog parameters are available in the **dbparm.sample.ini** file. Copy the parameters to the **dbparm.ini** configuration file.

[SYSLOG]
SyslogTranslatorFile=Syslog\PTA.xsl
SyslogServerPort=<port number>
SyslogServerIP=<server IP>
SyslogServerProtocol=UDP
SyslogMessageCodeFilter=295,308,7,24,31,428,361,372,373,359,436,412,411,300,302,294,427,471
UseLegacySyslogFormat=No

	2.	To forward Vault syslogs to multiple machines (for instance to your SIEM solution as well as to PTA), you can specify multiple values for the following parameters and separate each value with a comma.

	■	All destinations must use the same port and protocol, which are specified in the SyslogServerPort and SyslogServerProtocol fields.

	■	The specified values will apply to all destinations configured in SyslogServerIP, using the translator files specified in SysLogTranslatorFile.

Parameter Name	Comments
SyslogServerIP	
SyslogTranslatorFile	
UseLegacySyslogFormat	
SyslogMessageCodeFilter	Separate multiple values with a comma, and separate sets of multiple values with a pipe-line, as shown in the example below.

The following example shows how to send different syslog messages to multiple syslog servers.

[SYSLOG]
SysLogTranslatorFile=Syslog\Arcsight.sample.xsl,Syslog\QRadar.xsl,Syslog\PTA.xsl
SyslogServerPort=<port number>
SysLogServerIP=1.1.1.1,1.1.2.2,1.1.3.3
SyslogServerProtocol=UDP
UseLegacySyslogFormat=Yes,Yes,No
SyslogMessageCodeFilter=7,8,295|295-296|295,308,7,24,31,428,361,372,373,359,436,412,411,300,302,294,427,471

	3.	To send secured syslog data to PTA, see Configure Vault Trusted Connection to PTA.
	4.	Save the file and close it.
	5.	Restart the Vault.

For more detailed instructions about integrating SIEM applications, see Security Information and Event Management Applications.

Source: *https://docs.cyberark.com/pam-self-hosted/11.3/en/content/pta/configuring-vault-forward-syslog-messages.htm*

CyberArk PAM Integration Procedures

Please provide the following information to CyTech:

Requirements:Collect logs via syslog over UDP or TCP

*Syslog Host-> Syslog Collector IP address where the Elastic-Agent is installed.
*Syslog Port-> Port Number (Please identify if TCP or UDP)

If you need further assistance, kindly contact our support at **support@cytechint.com** for prompt assistance and guidance.

Revision #3
Created 16 January 2025 08:49:02 by Richmond Abella
Updated 17 January 2025 09:46:49 by Richmond Abella